

PRECONTRAI[®] 705

WIDTH: 270 cm	WEIGHT: 670 g/sqm
JUMBO ROLLS*: ± 350 lm	LENGTHS*: ± 30 lm



INFLATABLE PARTITIONS



TRUCK TARPULINS



TRAILER COVERS

GUARANTEES AND LABELS



ADVANTAGES

- **FERRARI[®] PRÉCONTRAI[®] TECHNOLOGY:**
 - EXCEPTIONAL DIMENSIONAL STABILITY
 - HIGH DURABILITY
 - EXCELLENT WELDABILITY
- **CONSIDERABLE MECHANICAL STRENGTH**
- **20 COLOURS AVAILABLE**
- **WIDE RANGE OF APPLICATIONS**
- **ANTI-THEFT OPTION WITH DEFENDER[®] (P. 44)**

COLOURS & REFERENCES (COLOURS ARE INDICATIVE)

	Ref. 705-1066	RAL 9016
	Ref. 705-1076	RAL 1015
	Ref. 705-1059	RAL 1018
	Ref. 705-1061	RAL 1003
	Ref. 705-1063	RAL 2004
	Ref. 705-1064	-
	Ref. 705-1065	RAL 3002
	Ref. 705-1050	RAL 5013
	Ref. 705-1051	RAL 5002
	Ref. 705-1052	RAL 5010
	Ref. 705-1053	RAL 5015
	Ref. 705-1054	RAL 6005
	Ref. 705-1055	RAL 6026
	Ref. 705-1069	RAL 7035
	Ref. 705-1070	RAL 7037
	Ref. 705-1071	RAL 7038
	Ref. 705-1072	RAL 7040
	Ref. 705-1267	Alu bright
	Ref. 705-1157	Alu dark
	Ref. 705-1075	RAL 9005

TECHNICAL SPECIFICATIONS

	PRÉCONTRAI[®] 705	STANDARDS
YARN	1100 dtex PES HT	TERSUISSE
WEIGHT	670 g/sqm	EN ISO 2286-2
WIDTH	270 cm	
TENSILE STRENGTH (WARP/WEFT)	280/280 daN/5 cm	EN ISO 1421
TEAR STRENGTH (WARP/WEFT)	30/30 daN	DIN 53.363
FLAME RETARDANCY	55 MM/MIN	ISO 3795
ADHESION	9/9 daN/5 cm	EN ISO 2411
FINISH	VARNISH BOTH SIDES	
HANDLING TEMPERATURE RANGE	-30°C/+70°C	
QUALITY MANAGEMENT SYSTEM		ISO 9001

The technical characteristics shown are average values given as a guide and may be modified.
*Our packaging data are given for information only and may vary as a function of manufacturing conditions.